

Philips Signage Solutions Q-Line Display

86" Direct LED Backlight Ultra HD

SignageSolutions



86BDL3650Q

Stand out from the crowd

Your versatile and easy-to-set-up 18/7 display

Inform and enthral with a Philips Q-Line 4K Ultra HD digital display. This reliable, easyto-install, Android powered signage solution is Wave-ready for remote management, putting you in full control, any time, anywhere.

Effortless setup. Total control.

- Optional Interact for wireless screen share
- Catch the Wave for revolutionary results
- **Cost-effective system solution**
- Easy control. Remotely manage networked displays
- · Easily schedule content from USB or internal memory

Smart and powerful

- Connect and control your content via the cloud
- Android SoC processor. Native and web apps
- WiFi connection made easy with optional CRD22 module

Versatile system solution

- Ultra-HD. Rich images. Stunning contrast
- FailOver. Ensure your display never goes blank



Highlights

SmartBrowser

Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Simply connect the display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists.

FailOver

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content on screen in the unlikely event of an input source or application failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

Integrated media player

Easily schedule content to play from USB or from internal memory. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

Interact (optional)

Wirelessly screen share using your existing Wi-Fi network to instantly and securely connect devices, or use our optional HDMI Interact dongle to cast directly onto the screen without connecting into the secured network.

Powered by Android 10

Powered by our Android 10 SoC platform, these hard-working Philips professional displays are optimised for native Android apps, and you can install web apps directly onto the display too. Flexible and secure, ensuring display specs stay up to the moment for longer.

PPDS Wave

Unlock the power, versatility and intelligence inside your Philips Q-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and set-up, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.







Specifications

Picture/Display

- Diagonal screen size: 85.6 inch / 217.4 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 400 cd/m²
- Contrast ratio (typical): 1200:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing angle (H / V): 178 / 178 degree
 Pixel pitch: 0.4935 x 0.4935 mm
- Display colors: 1.07 Billion
- Picture enhancement: 3/2 2/2 motion pull down, Progressive scan, Dynamic contrast enhancement
- Panel technology: IPS
- Operating system: Android 10
- Haze: 25%

Supported Display Resolution

 Computer formats Refresh rate Resolution 1920 x 1080 60Hz 1680 x 1050 60Hz 1600 x 1200 60Hz 1440×900 60H7 1280 x 1024 60Hz 1280×800 60Hz 1280 x 720 60Hz 60, 70, 75Hz 1024 x 768 1152×864 75Hz 60 Hz, 50 Hz 3840 x 2160 720 x 400 70Hz 800×600 56, 60, 72, 75Hz 800×600 56,60,72 Hz 832 x 624 75Hz Video formats Resolution Refresh rate 1080i 50, 60Hz 720_D

50,60 Hz 1080p 50. 60Hz 2160p 50. 60Hz

Connectivity

- Video input: USB 2.0 (x2), DVI-I (x 1), HDMI 2.0 (x2), USB 3.0 (x1)
- Audio input: 3.5 mm jack
- Audio output: 3.5mm jack
- External control: RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack, RJ45
- Other connections: micro SD, OPS

Convenience

- Keyboard control: Hidden, Lockable
- Network controllable: RS232, RJ45
- Signal loop through: RS232, IR Loopthrough
- Energy saving functions: Smart Power
- · Remote control signal: Lockable
- Tiled Matrix: Up to 3 x 3
- Placement: Landscape (18/7), Portrait (18/7)
- · Ease of installation: Smart Insert

Dimensions

- Bezel width: 15.5 mm (Even bezel)
- Set dimensions (W x H x D):
- 1929.0 x 1100.0 x 69.5mm(D@wall mount) / 91.8mm(D@handle) mm
- Set dimensions in inch ($W \times H \times D$): 75.94 x 43.31 x 2.74(@ wall mount)/ 3.61(@ handle) inch
- Product weight: 49.06 kg
- Product weight (lb): 108.16 lb
- Wall Mount: 600 mm x 400 mm, M8
- **Operating conditions**
- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20 ~ 80% RH (No condensation)
- Humidity range (storage) [RH]: 5 ~ 95% RH (No condensation)

Power

- Mains power: 100 240V~, 50/60Hz
- Standby power consumption: <0.5W
- Power Saving Features: Smart Power
- Consumption (Max): TBD
- Consumption (Typical): TBD W
- · Energy Label Class: G

Sound

• Built-in speakers: 2 x 10W RMS

Accessories

• Included Accessories: IR sensor cable (1.8 m) (x1), RS232 daisy-chain cable, Philips logo (x1), AC Power Cord, AC Switch Cover, Cable clip (x2), HDMI cable (1.8 m) (x1), Quick start guide, Remote control & AAA batteries, RS232 cable, USB Cover (x1)

Multimedia Applications

- USB Playback Video: H.264, H.263, H.265, MPEG1/
 - 2, MPEG4, VP8, VP9
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Audio: AAC, HEAAC, MPEG

Miscellaneous

- Warranty: 3 year warranty
- On-Screen Display Languages: Simplified Chinese, Traditional Chinese, English, French, German, Italian, Polish, Russian, Spanish, Turkish, Japanese, Arabic
- Regulatory approvals: CE, CB, FCC, Class A, VCCI, RoHS, UL

Internal Player

- CPU: Quad Core Cortex A55
- GPU: G52 MC1
- Memory: 16GB, 3GB DDR

© 2023 Koninklijke Philips N.V.

www.philips.com



Version: 1.0.1

All Rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 86386 EAN: 87 12581 79934 2

Issue date 2023-05-12

86BDL3650Q/00